




Products Pellet stoves

FP-45 (serial # 1355- +)

Technical specs



[Zoom picture](#)

[Features](#)

[Technical specs](#)

[Owner's manual](#)




CERTIFICATE OF QUALIFICATION

Eligible for the



ecoENERGY
Retrofit Program



Type of fuel	Pellets
Maximum recommended heating area	2,200 sq. ft.
BTU/H maximum	45,000
BTU/H minimum	8,200
Combustion autonomy on low	60 hours
Color	Metallic black
Exterior dimensions	25.5"W x 28"D x 33"H
Approved vent diameter	3" ou 4"
Loading capacity	80 lbs (36 kg)
Burn rate	1.3 to 5.5 lbs/hr.
Electrical consumption	2.5 Amps continuous duty
Electrical requirement	120 VAC - 60 hz - 15A
Choice of thermostatic or manual mode	Yes
Combustion technology	COMBEX
Number of intensity levels	6
Electronic igniter	Yes
Type of door	Glass with cast iron frame
Ash drawer	Yes
Minimum clearances (Sides)	6"
Minimum clearances (Back)	2"
Minimum clearances (Corners)	2"
Mobile home approved	Yes
Glass type	Ceramic glass
Glass surface	124 po. ca.
Weight	230 lbs (105 kg)
Warranty	Limited lifetime
Test standard - safety	ASTM-E1509, ULC S627-00, UL1482-98
Test standard - emissions	EPA Méthode 28